

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) UK Patent Application (19) GB (11) 2 294 821 (13) A

(43) Date of A Publication 08.05.1996

(21) Application No 9422263.5

(22) Date of Filing 04.11.1994

(71) Applicant(s)
GEC Alsthom Limited

(Incorporated in the United Kingdom)

PO Box 70, Mill Road, RUGBY, Warwickshire,
CV21 1TB, United Kingdom

(72) Inventor(s)
John Desmond Ainsworth
David Reginald Trainer
Philip John Fitz

(74) Agent and/or Address for Service
Henry Anthony Branfield
GEC Patent Department, Waterhouse Lane,
CHELMSFORD, Essex, CM1 2QX, United Kingdom

(51) INT CL⁶
H02J 3/18

(52) UK CL (Edition O)
H2F F14
G3U UEG U209 U210 U212
H2H HAB H23G H25G

(56) Documents Cited
GB 2152306 A GB 2103439 A GB 2057796 A
GB 1415634 A GB 1246703 A GB 1238015 A
GB 1137106 A US 4571535 A US 4470005 A

(58) Field of Search
UK CL (Edition N) G3U UEG, H2F FMAS FMAT FMAX
F14, H2H HAB
INT CL⁶ G05F 1/70, H02J 3/16 3/18, H02M 1/00
Online: wpi

(54) Multilevel converter

(57) A multilevel converter 30 for connection in shunt or in series with each phase of a single or multi-phase AC system is configured as a chain comprising a plurality of links, each of which comprises a voltage-commutated converter providing a multilevel AC voltage, and a main control arrangement for controlling a switching sequence of the voltage-commutated converter such as to provide a total voltage across the ends of the chain which is an aggregate of the individual multilevel voltages of the voltage-commutated converters. Each voltage-commutated converter may consist of a bridge and a DC source or sink. The DC source or sink may be either a capacitor, a battery or a DC-AC or AC-DC converter. The multilevel converter may also include voltage-balancing means to maintain desired absolute or relative voltage levels on the DC sources or sinks within the chain. The converter may include GTO or IGBT devices and various circuits are described (Figs. 7 - 15). The control arrangement to regulate the converter is described (Figs. 17 - 22). A capacitor clamping arrangement (Figs. 23 - 25) may be provided.




Figure 3




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 7




Figure 6






Figure 8

**Figure 9****Figure 10**




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15





Figure 16